

REMARKS

Claims 1-14 are pending in the application. The following objections and rejections to the application were given by the Examiner:

Claims / Section	35 U.S.C. Sec.	References / Notes
IDS	Objection	<ul style="list-style-type: none">• Illegible copies?
Priority	Objection	<ul style="list-style-type: none">• No receipt of certified copy
Drawings	Objection	<ul style="list-style-type: none">• Missing claim features
Specification	Objection	<ul style="list-style-type: none">• Typographical issues and clarification required
2	§112, Second Paragraph Indefiniteness	<ul style="list-style-type: none">• Unclear language
1-14	§103(a) Obviousness	<ul style="list-style-type: none">• Lerche, et al. (U.S. Patent No. 6,457,175); and• Sun, et al. (U.S. Patent No. 5,901,330).

5 Applicants have amended claims 1, 2 and 4, has added claim 15 for consideration, and has also provided discussion for distinguishing the present invention, with claims as amended, from the art cited against it.

Applicants' use of reference characters below is for illustrative purposes only and is not intended to be limiting in nature unless explicitly indicated.

10 **INFORMATION DISCLOSURE STATEMENT OBJECTION**

1. Applicants are resubmitting the Information Disclosure Statement along with legible copies of the references concurrently herewith for consideration by the Examiner.

15 In response to the comments made by the Examiner on p. 2 of the OA, under numbered paragraph 1, Applicants are resubmitting the Information Disclosure Statement, along with legible copies of the references so that these

references may be considered by the Examiner. Applicants believe the Examiner is referring to the IDS submitted on February 26, 2004 and not to one filed on March 28, 2001. Applicants are providing, in Appendix A, proof, in the form of a stamped postcard received from the U.S. Patent Office, that the IDS
5 and appertaining 5 references with PTO-1449 form were received by the PTO on March 1, 2004. If the objection was related to the illegibility of a particular reference, Applicants ask that a more detailed description of the deficiency be provided in the next Office Action or that the Examiner contact the Applicants' representative to help resolve the matter.

10

PRIORITY DOCUMENT MISSING

2. Applicants are resubmitting a certified copy of the Priority Application for entry in the file.

15

In response to the comments made by the Examiner on p. 2 of the OA, under numbered paragraph 2, Applicants are resubmitting a certified copy of the Priority Application to perfect priority in this application. Applicants are providing,
in Appendix B proof, in the form of a stamped postcard received from the U.S. Patent Office, that the Submission of the Priority Application were received by the PTO on March 27, 2001.

DRAWING OBJECTION

20

3. Applicants are amending the drawings to include a new Figure 2 illustrating the inventive method steps as claimed.

In response to the comments made by the Examiner on p. 2 of the OA, under numbered paragraph 3, Applicants are amending the drawings to include a

new Figure 2 (attached in Appendix C) illustrating the inventive method steps, as claimed. Since the new drawing figure contains no additional information beyond what is disclosed in the claims and appertaining descriptive portion of the Specification, Applicants believe that no new matter has been added by this
5 drawing addition.

SPECIFICATION OBJECTION

4. Applicants have amended the Specification in accordance with the Examiner's suggestions, where appropriate, and provided discussion addressing other objections.

10 The points are addressed below, referring to points 1-10 as sequentially indicated on pages 3-4 of the OA. Applicants believe that the Specification has been amended without the addition of any new matter to the application.

Point 1—The Specification has been amended to refer to the correct memory block.

15 Point 2—The Specification has been amended to clarify the relevant function/action and the state to which this time frame references.

Point 3—The Specification has been amended to clarify that either a checksum on the loaded program as a whole or checksums for each of the relevant parts could be utilized. This aspect is not required to support any of the
20 claims currently in the application.

Point 4—The Specification has been amended to clarify what the checksum is compared to and does not constitute the addition of new matter as the mechanisms for working with checksums is known in the art.

Point 5—The Specification is silent on the handling of an error if there is a problem with the connection program, although one of skill in the art would recognize only two possibilities: 1) that this is an irrecoverable error and would require service by repair personnel; or 2) that this is a recoverable error and would thus require that the original (uncorrupted) connection program be stored in non-volatile memory or in a “verified” memory location. Since none of the claims rely on this feature, there are no enablement concerns of the claims.

Point 6—The Specification has been amended to include the clarifying reference character.

Point 7—The Specification has been amended to clarify the point in time to which the successive described steps occur.

Point 8—The Specification has been amended to clarify that the memory areas not described as being overwritten (fifth and sixth memory blocks, respectively containing the connection program VP and the boot program BP) constitute the “protected” and “safely stored” areas containing the basic elements of the operating system.

One of skill in the art would recognize that without a boot program or basic connection program, the device would almost be worthless (presuming no user would want to key in a boot program by hand).

Point 9—See comments for Point 8.

Point 10—References to the drawing and drawing reference characters have been added to the Specification. No new matter has been added thereby.

35 U.S.C. §112, SECOND PARAGRAPH, CLAIM 2 INDEFINITENESS

5. Claims 2 and 4 have been amended to more particularly point out and distinctly claim the subject matter regarded as the invention.

Claim 2 has been amended to indicate that establishing a connection
5 comprises utilizing a portion of the operating system for establishing the connection. In a preferred embodiment of the invention, the connection program part VP is utilized to establish the connection (see paragraphs [0018] and [0019]), which clearly is a part of the operating system. However, the amended language is broadly worded so that it is not limited solely to the connection
10 program part VP as illustrated in the Specification. Claim 4 has been similarly amended.

Applicants believe that this amendment sufficiently points out and distinctly claims the subject matter of the invention and respectfully requests that the 35 U.S.C. §112 rejection be withdrawn from the application.

15 35 U.S.C. §103(a), CLAIMS 1-14 OBVIOUSNESS OVER LERCHE IN VIEW OF SUN

6. Claim 1 has been amended to clarify the distinction of the present invention over Lerche and Sun. Applicants have added new claim 15 for consideration by the Examiner.

Claim 1 has been amended to include the limitation that the connection
20 establishment and transmission of the operating system data occurs utilizing only call signaling methods of the telecommunication terminal device. Support for this amendment can be found in the Specification at paragraphs [0019] and [0020].

The main idea of the invention is to remotely update the operating system of a telecommunication terminal device itself (i.e., a telephone) using the call signaling of the device itself to make a connection to a "data management center". This data management center holds the latest copy of operating system of the specific telecommunication terminal device and after some security checks the content is transferred via call signaling methods to the telecommunication equipment (e.g., known signaling methods such as User Information in case of ISDN or, e.g., containers for SIP/H.323 within the call signaling—not described or specifically claimed, but well known in the art). Sun describes a different method of updating the in-circuit program by using an external device, and Lerche describes an upgrading-method which uses a modem.

In the present invention, with claims as amended, a method for updating the telecommunication terminal device software is described that uses only the call signaling itself. According to the invention, a method is described that is able to update the telecommunication terminal device software from any server of the "data management center" within the network. This differs also from SUN et al., which describe a method of updating the software locally by connection it to an external device.

The invention also relates to the connection establishment part, which is safely stored within the memory of the telecommunication terminal device as a kind of "mini operating system" and cannot be overwritten, which ensures a safe software download mechanism even if during the update phase a connection failure or loss occurs.

The prior art references do not disclose the usage of the call signaling methods for updating a telecommunication terminal device. Therefore the invention is new.

Furthermore the documents of the state of the art describe only updating
5 methods which make use of external devices or modems. They do not teach or suggest using call signaling methods for the updating procedure. Therefore the invention, with claims as amended, is not obvious for one of ordinary skills of the art.


For these reasons, the Applicant asserts that the amended claim
10 language clearly distinguishes over the prior art, and respectfully request that the Examiner withdraw the §103(a) rejection from the present application.

CONCLUSION

Inasmuch as each of the objections have been overcome by the amendments, and all of the Examiner's suggestions and requirements have been
15 satisfied, it is respectfully requested that the present application be reconsidered, the rejections be withdrawn and that a timely Notice of Allowance be issued in this case.

Respectfully submitted,

20

 (Reg. No. 45,877)

Mark Bergner
SCHIFF HARDIN, LLP
PATENT DEPARTMENT
6600 Sears Tower
Chicago, Illinois 60606-6473
(312) 258-5779
Attorney for Applicants
Customer Number 26574

25

Appl. No. 09/734,938
Reply to Office Action of April 8, 2004



CERTIFICATE OF MAILING

I hereby certify that this correspondence is being deposited with the United States Postal Service as First Class Mail in an envelope addressed to: Mail Stop Non-Fee Amendment, Commissioner for Patents, PO Box 1450,
5 Alexandria, VA 22313-1450 on July 8, 2004.


Mark Bergner Attorney for Applicants

10

METHOD FOR MODIFYING THE OPERATING SYSTEM OF A TELECOMMUNICATION TERMINAL DEVICE

BACKGROUND OF THE INVENTION

FIELD OF THE INVENTION

[0001] The present invention is generally directed to a telecommunication terminal device. In particular, the present invention is directed to modifying an operating system used in a telecommunication terminal device.

DESCRIPTION OF THE RELATED ART

[0002] In order to meet the increasing and rapidly changing demands made of telecommunication terminal devices, there is a need to make the terminal devices more reliable and adaptive to advances in technology. Often this is done by modifying or completely replacing the operating system used in the telecommunication terminal device. Such modification or replacement allows the telecommunication terminal device to remain useful to the user for a greater period of time and through several advances in technology.

[0003] Also, as telecommunication terminal devices are increasingly more involved in the transmission of data over a telecommunication network, proper modification of the operating system used by the telecommunication terminal device would make such data transmission easier.

[0004] A constant connection between a telecommunication terminal device and a telecommunication network that carries data is necessary in order to ensure reliable transfer of the data over the network to the telecommunication terminal device. However, as can well be appreciated, a constant connection cannot be assured for the entire duration of the data transmission due to the ever increasing burden placed on communication networks, and previously known methods of verifying data transmission do not offer a way to take an interruption of the connection into consideration or correct errors in the data transmission that thereby

occur. This can be a major problem and source of frustration for both the sender of the data as well as for the intended recipient.

[0005] Moreover, operating systems used by telecommunication terminal devices have been known to fail occasionally, and any telecommunication terminal device on which an operating system has failed makes the terminal device no longer functional. Hence, the terminal device must be handed over to the manufacturer for repair or a replacement for the device must be made. In the case of repair, even under the best of circumstances, the manufacturer can restore the malfunctioning telecommunication terminal device to near factory-new condition. However, the repair process involves great inconvenience for the user of the telecommunication terminal device, since comparatively long processing times are usually experienced. Further, the telecommunication terminal device must be transported over relatively great distances due to the increasing centralization of the manufacturers. In the case of replacement, the user of the telecommunication terminal device would probably incur an undesired and untimely capital expenditure. In either event, repair or replacement, failure of the operating system in a telecommunication terminal device is an unpleasant and unwelcome inconvenience to the user.

[0006] Therefore, in order to overcome all of these shortcomings, the present invention offers an inexpensive, dependable and convenient way for modifying the operating system of a telecommunication terminal device, as well as for allowing the telecommunication terminal device to check for errors in a data transmission and correct any errors found.

SUMMARY OF THE INVENTION

[0007] It is an object of the present invention to provide a method for modifying the operating system of a telecommunication terminal device.

[0008] It is a another object of the present invention to provide a method for checking the correctness of data transmitted over a telecommunications network.

[0009] It is a further object of the present invention to provide a method for correcting errors in a data transmission, even if the error is attributed to an interruption of a telecommunications connection.

[0010] It is an additional object of the present invention to provide a method for periodically repeating a data transmission so that the current status of the operating system can be verified.

[0011] It is yet another object of the present invention to provide a method for monitoring a data transmission by forming and checking a checksum derived from the transmitted data.

[0012] It is yet a further object of the present invention to provide a method for checking the correctness of a data transmission with the assistance of the operating system running on the telecommunication terminal device.

[0013] It is yet an additional object of the present invention to provide a method for not overwriting the entire memory area used by the operating system of a telecommunication terminal device during a data transmission.

[0014] It is still another object of the present invention to provide a method for data transmission having high degree of reliability.

[0015] These and other objects of the present invention will become apparent upon careful review of the following disclosure, which is to be read in conjunction with review of the accompanying drawing figure.

BRIEF DESCRIPTION OF THE DRAWING

[0016] Various embodiments of the invention are described below and with reference to the drawings.

Figure 1 shows is a block diagram of a memory area according to an embodiment of the present invention; and

Figure 2 is a flowchart illustrating the basic steps according to an embodiment of the present invention.

DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENTS

[0017] Figure 1 shows, in block diagram form, the division of a memory area used for the operating system of a telecommunication terminal device and the conditions of the memory area during the loading of a modified operating system according to the present invention.

[0018] The memory area is divided into six memory blocks B1, B2, B3, B4, B5, B6, each memory block being of equal size to the others. First through third memory blocks B1, B2, B3 contain first through third program parts P1, P2, P3, respectively. A reserved memory R is situated in the fourth memory block B4. The fifth memory block B5 contains a connection program part VP which is needed for the connection setup. Finally, a boot program BP is located in the sixth memory block B6. This occupancy of the memory area is referred to as first condition Z1.

[0019] The user of the telecommunication terminal device selects the access number of the data management center that administers the operating system data (Figure 2, step S1), such as by dialing into, and ~~subsequently~~ subsequently starts the data transfer: step S2. At first, the connection program VP from the ~~sixth~~ fifth memory block B65 is copied into the first memory block B1. This occupancy of the memory area is referred to as second condition Z2. Subsequently, a second new program part NP2 is transmitted into the second memory block B2, a third new program part NP3 is transmitted into the third memory block B3. Then, a first new program part NP1 is transmitted into the fourth memory block B4. 4 (collectively, step S3). This memory occupancy is referred to as third condition Z3. Last, the first new program part NP1 is copied into the first memory block B1. The memory occupancy resulting therefrom is referred to as a fourth condition Z4.

[0020] ~~To begin~~ After the new program parts NP1-NP3 have been transmitted and occupy memory blocks B1-B3 (i.e., after the fourth condition Z4), the user of the telecommunication terminal device initiates a restart of the operating system. The program execution begins with the boot program BP with which the correctness of the newly loaded program parts NP1, NP2, NP3 is determined by the

formation and comparison of a checksum, of a calculated checksum and comparison with a known and predetermined checksum on either each new part or on all new parts combined and taken as a whole (step S4).

[0021] In the absence of an error as determined by the proper comparison of the checksum, further program execution is continued at the first memory block B1 and at the first new program part NP1. In the case of an error, the correctness of the connection program VP is determined by forming and comparing a checksum.

[0022] If the outcome of this check reveals no errors, then the connection program VP is copied into the first memory block B1 and the program execution is again continued at the first memory block B1, both in the third condition Z3 as well as in the second condition Z2. After which the successful determination of the correctness of the connection program VP, a branch is made to the connection program VP with the boot program BP. This results in a renewed connection setup to the data management center (step S6) and another data transmission (step S7). The steps of this sequence are repeated until a correct version of the new program parts NP1, NP2, NP3 has been communicated into the memory of the telecommunication terminal device. These basic component parts are all that are needed for checking for errors in the data transmission.

[0023] Basic elements of the operating system are safely stored in protected memory areas of the telecommunication terminal device . As described above, the first through fourth memory blocks have been overwritten, but the fifth and sixth memory blocks described above have remained intact. The fifth memory block contains the connection program VP and the sixth memory block contains the boot program—therefore, these two blocks constitute the basic elements of the operating system. Thus, the entire memory area containing the operating system is not overwritten by the data transmission and a falsification of the corresponding data is prevented.

[0024] A copy of at least a part of the operating system is compiled before the data transfer is completed. In addition, the operating system modified by

the data transfer is activated only when the data transmission is correct. In this way, a faulty version of the operating system is prevented from being communicated to the telecommunication terminal device due to an incorrect data transmission. Over and above this, a correct, although not updated, version of the operating system can be accessed and faultless function of the telecommunication terminal device can be assured. According to the present invention, this simple procedure is all that is needed for checking a data transmission over a telecommunication network using the telecommunication terminal device.

[0025] The data management center expects an answerback from the tele-communication terminal device regarding the correctness of the data transmission and restarts the data transmission after a predetermined time if the answerback is not received. Although the data management center fails to receive an answerback from the telecommunication terminal device regarding the correctness of the data transmission, it is the telecommunication terminal device that requests that the data management center retransmit the data. Therefore, only the telecommunication terminal device is needed to detect an error in transmission and to have a repeat of the data transmission initiated. Also, initiation of a renewed data transmission is also possible even in the event of nearly complete destruction of the operating system.

[0026] Once a data transmission is undertaken, the transmission is repeated periodically. In this way, the current status of the operating system is also transmitted into the data memory of the telecommunication terminal device. Monitoring the data transmission is therefore accomplished by forming and checking a checksum derived from the communicated data.

[0027] A connection between the telecommunication terminal device and the data management center is established with the assistance of the operating system running in the telecommunication terminal device. In this case, a decision is made by the telecommunication terminal device as to whether a connection is necessary. If a connection is necessary, one can be established as warranted. If a determination is made not to establish a connection, the telecommunication terminal

device assumes a stand-by mode in preparation for the next data transmission that may require a connection.

[0028] An operating system modified according to the present invention permits the correctness of transmitted data to be checked locally in the ~~telecommuni-cation~~telecommunication terminal device without involving the data management center. This centralized approach, assures that the burden of checking for errors in a data transmission is taken away from both the data management center, as well as the telecommunication network. This is true, because as explained above, only a minimum amount of data need be transmitted to the telecommunication terminal device in order to check for errors in the transmission.

[0029] When the correctness of the data transmission is checked and the data transmission is repeated, as in the case of error, the first connection is aborted and a new connection is set up between the telecommunication terminal device and the data management center of the telecommunication network. This occurs even if the error is attributed to an interruption of the connection between the telecommunication network and the telecommunication terminal device are taken into consideration and corrected. As can readily be appreciated, interruption in a connection cannot be entirely precluded given the current state of the art of the telecommunications.

[0030] The present invention is capable of modifying programs which are needed for processing communication protocols such as calling line identification ~~restrie-tion~~restriction (CLIR), call-waiting (CW) and call-back-when-busy (CCBS) that are normally found in the operating system of a telecommunication terminal device.

[0031] The present invention is useful with respect to telecommunication network transmission of voice, such as using Internet protocol. Such IP telephony is very attractive to user of telecommunication terminal devices due to the growing burden placed upon classic voice networks because of the increase in traffic over these networks. When used for an IP telephony transmission, the present invention regards the digitized voice signal as the data transmission, as discussed above.

[0032] The present invention is also useful when an integrated services digital network (ISDN) telephone is used as the telecommunication terminal device. This is because an ISDN telephone enables a plurality of desirable services to be made available to the user. In which case, the present invention gives the user the opportunity to easily modify the operating system of the ISDN telephone, as well as to check for errors in data transmission.

[0033] The present invention is also useful when a personal communications service (PCS) telephone, a wireless telephone, a cellular telephone, or other such mobile telephone is used as the telecommunication terminal device. Even more than in the case of the use of an ISDN telephone, the function and usefulness of these devices is determined by rapidly changing user demands. Thus, the present invention is suitable for implementing desirable and necessary modifications to the operating system of these types of telephones, as well as to check for errors in data transmission.

[0034] Although preferred embodiments of the invention have been described herein, it is to be understood that the invention is not limited to these embodiments, and that various changes and modifications thereto may be made without departing from the scope or spirit of the invention, which is defined by the following claims.

ABSTRACT OF THE DISCLOSURE

In a telecommunication network having a data management system, a method for modifying the operating system of a telecommunication terminal device connected to the network. An operating system modified according to the method allows the telecommunication terminal device to check for errors in a data transmission. If an error in the data transmission is found, connection between the terminal device and the network's data management system is aborted, a new connection between the terminal device and the network's data management system is made, and the data transmission is repeated.